

# OMNI<sup>®</sup> Universal Ignitor

## The Only Universal Ignitor

OMNI<sup>®</sup> mounts onto any previously installed ignitor mounting plates and eliminates need for extra mounting plates. It makes your service calls quick and easy, and ships complete with required hardware.

### Absolute Maximum Ratings

Model #	2270	2275	2280
Input Supply Voltage (V)	12 Vdc	108-132	216-252
Input Current (A)	2.5		
Input Supply Frequency (Hz)		50/60	50/60
Primary Voltage - Amperes (VA)		86.5	86.5
Secondary Voltage (kV peak)	20.0	17.5	17.5
Secondary Frequency (kHz)	>18	20	20
Secondary Short Circuit Current (mA)	20	45	45
Storage Temperature (degrees C)	-40 to +80	-40 to +80	-40 to +80
Operating Temperature (degrees C)	-30 to +65	-30 to +40	-30 to +40
Operating Relative Humidity (%)	90	90	90
Loading Air Gap (inches)	1/16 - 3/16	1/16 - 3/16	1/16 - 3/16



[www.allanson.com](http://www.allanson.com)

**USA** | 99 Adams Blvd. | Farmingdale, New York | 11735  
 Phone: 631-293-3880 | Fax 1-631-293-3470

**CANADA** | 33 Cranfield Road | Toronto, Ontario | M4B 3H2  
 Phone: 416-755-1191 | Toll-Free 1-877-264-8444 | Fax 1-877-278-0907