

COMMERCIAL GAS MODELS



LIGHT DUTY ATMOSPHERIC VENT

Light Duty Atmospheric Vent models are perfect for smaller commercial applications that require more recovery than a residential water heater, but not as much as a larger commercial unit. Each of these models combines energy saving performance with the durability to withstand the day-to-day demands of commercial water heating. Light Duty Atmospheric Vent models are also available in Ultra Low NOx Eco-Defender Safety System® versions.

APPLICATIONS:

Fast food restaurants and office buildings

FEATURES:

full descriptions are available in glossary beginning on page 33

- ICON System™ Control
- ICON System™ Accessory Package Compatible
- OnGuard RMT™ System Compatible – Accessory Module Required
- Defender Safety System®
- Hydrojet® Total Performance System
- Vitraglas® Lining
- ¾" NPT Dielectric Waterway Fittings
- Max Temp - 180°F
- NSF Construction Available
- Side Connections
- Factory Installed Heat Traps
- Snap Lock Draft Diverter
- Protective Magnesium Anode Rod
- Low Restriction Brass Drain Valve
- T&P Relief Valve Installed
- 2" Non-CFC Foam Insulation
- 3-Year Limited Tank Warranty—can be upgraded to 5-Year at additional cost

Model Number	Capacity U.S. Gal.	Input		Recovery at 100°F Rise*		Floor to Vent Conn. in.	Jacket Dia. in.	Vent Size in.	Approx. Shipping Weight lbs.
		Nat. BTU/Hr.	LP BTU/Hr.	Nat. U.S. GPH	LP U.S. GPH				
50T-65FB-3N	48	65,000	61,000	63	59	59¼	22	4	164
65T-65FB-3N	65	65,000	63,000	63	61	63	24	4	205

These models are not recommended for sanitation purposes.

For Propane (LP) models change suffix "B" to "S" and "N" to "X" (Example: 50T-65FS-3X)

*Based on manufacturers rated recovery efficiency.

