

BYO – Using Blue Hose™, SnapFast®, Restraining Device

Build your own custom Safety System, using the Blue Hose™ as your integral system component – and adding your desired specifications to it as well as the accessories you want to meet the specific needs of your application.

PART NUMBER EXPLANATIONS	
1650	1/2" dia. Blue Hose
1675	3/4" dia. Blue Hose
16100	1" dia. Blue Hose
16125	1-1/4" dia. Blue Hose
B	Braided
P	PVC Coated (with Antimicrobial Coating)
Q	Quick-Disconnect (SnapFast)
CF	Safety Quik Quick-Disconnect Valve
S	Swivel MAX Rotational Fitting
2S	Double Swivel MAX
R	Restraining Device & Hardware
24	24" Connector Length
36	36" Connector Length
48	48" Connector Length
60	60" Connector Length
72	72" Connector Length
PS	Placement System (Safety-Set)

NOTES:

1. Safety Quik (CF) is a combination quick-disconnect and valve fitting, so a full port valve is not shipped with kits including Safety Quik.
2. For each Swivel MAX (S) selected, one elbow will be removed from the kit.
3. Moveable connectors and kits are located on pages 6–9. To order 12" connectors, contact Dormont Customer Service – 800-367-6668.
4. To include Safety-Set®, add PS to the end of the kit part number. (See Page 10)
5. SnapFast is not for use in temperatures lower than 32°F (0°C) and is for indoor use only.



BTU/hr†	ID	PART #	Blue Hose	Snap-Fast	Swivel MAX	Swivel MAX (2)	Safety Quik	Full-Port Valve	Elbows (2)	Elbow	Restraining Device	Safety-Set
---------	----	--------	-----------	-----------	------------	----------------	-------------	-----------------	------------	-------	--------------------	------------

Blue Hose Safety Systems with SnapFast

55k	1/2"	1650BPQ72	√	√						√		
60k	1/2"	1650BPQ60	√	√						√		
68k	1/2"	1650BPQ48	√	√						√		
77k	1/2"	1650BPQ36	√	√						√		
87k	1/2"	1650BPQ24	√	√						√		
139k	3/4"	1675BPQ72	√	√						√		
158k	3/4"	1675BPQ60	√	√						√		
180k	3/4"	1675BPQ48	√	√						√		
218k	3/4"	1675BPQ36	√	√						√		
232k	3/4"	1675BPQ24	√	√						√		
279k	1"	16100BPQ72	√	√						√		
294k	1"	16100BPQ60	√	√						√		
334k	1"	16100BPQ48	√	√						√		
379k	1"	16100BPQ36	√	√						√		
414k	1"	16100BPQ24	√	√						√		
419k	1-1/4"	16125BPQ72	√	√						√		
476k	1-1/4"	16125BPQ60	√	√						√		
541k	1-1/4"	16125BPQ48	√	√						√		
615k	1-1/4"	16125BPQ36	√	√						√		
699k	1-1/4"	16125BPQ24	√	√						√		

Blue Hose Safety System with SnapFast & Restraining Device

55k	1/2"	1650BPQR72	√	√						√	√	
60k	1/2"	1650BPQR60	√	√						√	√	
68k	1/2"	1650BPQR48	√	√						√	√	
77k	1/2"	1650BPQR36	√	√						√	√	
87k	1/2"	1650BPQR24	√	√						√	√	
139k	3/4"	1675BPQR72	√	√						√	√	
158k	3/4"	1675BPQR60	√	√						√	√	
180k	3/4"	1675BPQR48	√	√						√	√	
218k	3/4"	1675BPQR36	√	√						√	√	
232k	3/4"	1675BPQR24	√	√						√	√	
279k	1"	16100BPQR72	√	√						√	√	
294k	1"	16100BPQR60	√	√						√	√	
334k	1"	16100BPQR48	√	√						√	√	
379k	1"	16100BPQR36	√	√						√	√	
414k	1"	16100BPQR24	√	√						√	√	
419k	1-1/4"	16125BPQR72	√	√						√	√	
476k	1-1/4"	16125BPQR60	√	√						√	√	
541k	1-1/4"	16125BPQR48	√	√						√	√	
615k	1-1/4"	16125BPQR36	√	√						√	√	
699k	1-1/4"	16125BPQR24	√	√						√	√	

† Minimum Flow Capacity (0.64 Sp. Gr., 1000 BTU/ft³ Natural Gas at 0.5" wc pressure drop)