

BYO – BUILD-YOUR-OWN SAFETY SYSTEM

BYO – Using BlueHose™, Safety Quik®, and Swivel MAX®



BTU/hr†	ID	PART #	Blue Hose	Snap-Fast	Swivel MAX	Swivel MAX (2)	Safety Quik	Full-Port Valve	Elbows (2)	Elbow	Restraining Device	Safety-Set
---------	----	--------	-----------	-----------	------------	----------------	-------------	-----------------	------------	-------	--------------------	------------

Blue Hose Safety Systems with SnapFast & Swivel MAX

51k	1/2"	1650BPQS72	√	√	√					√		
56k	1/2"	1650BPQS60	√	√	√					√		
63k	1/2"	1650BPQS48	√	√	√					√		
72k	1/2"	1650BPQS36	√	√	√					√		
81k	1/2"	1650BPQS24	√	√	√					√		
130k	3/4"	1675BPQS72	√	√	√					√		
147k	3/4"	1675BPQS60	√	√	√					√		
167k	3/4"	1675BPQS48	√	√	√					√		
203k	3/4"	1675BPQS36	√	√	√					√		
216k	3/4"	1675BPQS24	√	√	√					√		
260k	1"	16100BPQS72	√	√	√					√		
274k	1"	16100BPQS60	√	√	√					√		
310k	1"	16100BPQS48	√	√	√					√		
353k	1"	16100BPQS36	√	√	√					√		
385k	1"	16100BPQS24	√	√	√					√		
460k	1-1/4"	16125BPQS72	√	√	√					√		
463k	1-1/4"	16125BPQS60	√	√	√					√		
482k	1-1/4"	16125BPQS48	√	√	√					√		
491k	1-1/4"	16125BPQS36	√	√	√					√		
535k	1-1/4"	16125BPQS24	√	√	√					√		

Blue Hose Safety Systems with SnapFast, Swivel MAX, & Restraining Device

51k	1/2"	1650BPQSR72	√	√	√					√	√	
56k	1/2"	1650BPQSR60	√	√	√					√	√	
63k	1/2"	1650BPQSR48	√	√	√					√	√	
72k	1/2"	1650BPQSR36	√	√	√					√	√	
81k	1/2"	1650BPQSR24	√	√	√					√	√	
130k	3/4"	1675BPQSR72	√	√	√					√	√	
147k	3/4"	1675BPQSR60	√	√	√					√	√	
167k	3/4"	1675BPQSR48	√	√	√					√	√	
203k	3/4"	1675BPQSR36	√	√	√					√	√	
216k	3/4"	1675BPQSR24	√	√	√					√	√	
260k	1"	16100BPQSR72	√	√	√					√	√	
274k	1"	16100BPQSR60	√	√	√					√	√	
310k	1"	16100BPQSR48	√	√	√					√	√	
353k	1"	16100BPQSR36	√	√	√					√	√	
385k	1"	16100BPQSR24	√	√	√					√	√	
460k	1-1/4"	16125BPQSR72	√	√	√					√	√	
463k	1-1/4"	16125BPQSR60	√	√	√					√	√	
482k	1-1/4"	16125BPQSR48	√	√	√					√	√	
491k	1-1/4"	16125BPQSR36	√	√	√					√	√	
535k	1-1/4"	16125BPQSR24	√	√	√					√	√	

NOTES:

- To include Safety-Set®, add PS to end of the part number. (See Page 10)
- 3/4" and 48" models are available for Quick Ship 24.
- SnapFast and Swivel MAX are not for use in temperatures lower than 32°F (0°C) and are for indoor use only.

† Minimum Flow Capacity (0.64 Sp. Gr., 1000 BTU/ft³ Natural Gas at 0.5" wc pressure drop)