

GV Series 3 Trim



GV Series 3 Trim

| Fig. No. | Part No. | Description | Mfr. | Mfr's Part No. |
|---|-------------|---|-------------|--------------------|
| 1 | 510-312-021 | High limit temperature control, SPST, automatic recycle, 140-220°F, Range 30°F fixed differential, 1/2" N.P.T. brass control well. | Honeywell | L4080D-1228 |
| 2 | 511-546-920 | ASME Pressure relief valve, 30 PSIG, 3/4" N.P.T. male inlet, brass, side 3/4" N.P.T. female outlet | Watts | M330 |
| 3 | 510-218-099 | Combination Pressure-Temperature Gauge, 2 1/2" Dial, 0-60 PSIG, 70-250°F, short shank, back connection, 1/4" N.P.T. Spec. 199994 | ENFM | 4104 |
| | Ametek | | PT 1088 | |
| | 510-218-047 | Combination Pressure-Temperature Gauge, 2 1/2" Dial, 0-60 PSIG, 70-250°F, short shank, back connection, 1/4" N.P.T. Spec. 199994, with shut-off | ENFM | 4104-3-1/2-60 |
| 4 | 511-246-392 | Drain valve, 3/4" N.P.T., 1 1/2" shank, brass | Hammond | 710 |
| 5 | 511-405-113 | System Circulator, 1/25 HP, 120/60/1 motor, 1,750 RPM, 0.75 AMPS | Taco | 007F |
| | | Bypass Circulator, 1/25 HP, 120/60/1 motor, 1,750 RPM, 0.75 AMPS | Taco | 007F |
| 6 | 590-317-543 | Circulator gasket | Taco | 110-339 |
| 7 | 381-354-525 | 1" Universal hardware kit (Includes: flange, gasket, screws and nuts) | Weil-McLain | |
| 8 | 591-391-824 | Wiring harness, dual circulators to control module | Weil-McLain | |
| | 560-742-938 | Cooper return bend, 1", requires 2-1" NPT x 1" sweat adapters which can be obtained locally | Weil-McLain | |
| | 511-330-089 | Water temperature sensor and clamp with 12" leads | Keystone | JW4465 |
| | | | UT | JW4465 |
| 11 | 382-200-375 | Block temperature switch 350° open - 250° close | Elmwood | 2455 RC-174-113 |
| Additional Water Trim Components | | | | |
| 12 | 510-148-565 | Coin vent, 1/8" N.P.T. (Reducing coupling required) | Keeney | #4SN |
| 13 | 510-632-088 | Fill-Trol Diaphragm Expansion Tank, (Tank Only) with "O" Ring and special thread connection to fill valve | Amtrol | 109 |
| | 510-632-089 | Fill-Trol Diaphragm Expansion Tank, (Tank Only) with "O" Ring and special thread connection to fill valve | Amtrol | 110 |
| 14 | 511-210-433 | Fill Valve, angle style – 90° with built in strainer, pressure reducer, check valve, and manual shut-off | Conbraco | MX3907 |
| | 382-200-420 | Fill-Trol Package, tank kit with fittings | Amtrol | 109 |
| | 382-200-425 | Fill-Trol Package, tank kit with fittings | Amtrol | 110 |